



IXI 4

This satellite station has been designed for filming sports and other major events which require an agile, flexible technical set-up.

Eutelsat registration: **F512**

Coordination: **+33 (0) 6 35 12 17 71**

N-1: **+33 (0) 6 46 81 03 33**



Multi-camera filming
with up to 4 cameras



2+1 SD/HD MPEG2 / MPEG4
Adaptable on request



Tri phase 32 Amp
5kVA UPS EATON
1 x 15 kVA generator



Mercedes Sprinter 519
DT-277-FB

Lengths 7.40 m

Widths 2.00 m

Height 3.30 m





HDTV DSNG unit

Uplink:

- 2+1 SD/HD MPEG2/MPEG4
- 3 Encoders Modulators ATEME CM5000

MPEG2 / MPEG 4 - SD / HD
DVB-S / DVB-S2

- 2 IRD's Ateme DR5000

MPEG2 / MPEG 4 - SD / HD
DVB-S / DVB-S2

- 2 Enhancers SSPA Advantech 250W - Phase Combine
- Antenna AVL 1,80m 1812K
- Spectrum analyzer Rohde & Schwarz FSH-3

Production:

- Riedel System of routing/monitoring/Up-Down-Cross
Audio/Video conversion:
3G/HD/SD - MADI/AES/ANALOG/DMUX/MUX
Mediornet Modular + Mediornet Compact
- Control System L-S-B VSMstudio + Panel
- Intercom matrix 16 ports + MADI Riedel Artist32 card
- Technical Monitoring VTM4100 (integrated Dolby E)
- Mixing table Yamaha DM1000 with MADI card
- 2 Bridges 2W GSM
- 2 Inserts RTC Telos
- Prewiring for Codec RNIS
- Multi-camera configuration on request

Contact:

Bernard Birebent
+33 (0)6 08 43 60 51
bernard.birebent@ampvisualtv.tv

www.ampvisualtv.tv/en/