



IXI 6

This satellite station has been designed to respond to customer demand and can be rolled out to short dead-lines.

Eutelsat registration: **F224**

Coordination: **+33 (0) 6 13 87 75 30**

N-1: **+33 (0) 6 16 24 25 80**



Single-camera captation



2+1 SD/HD MPEG2 / MPEG4
Adaptable on request



Monophase 32 Amp
5kVA Fisher Panda generator



Volkswagen Transporter
DF-929-KH

Lengths 5.70 m

Widths 1.84 m

Height 2.50 m





HDTV DSNG unit

Uplink:

- 2+1 SD/HD MPEG2/MPEG4
- 3 Encoders Modulators ATEME CM5000

MPEG2 / MPEG 4 - SD / HD
DVB-S / DVB-S2

- 2 IRD's Ateme DR5000

MPEG2 / MPEG 4 - SD / HD
DVB-S / DVB-S2

- 2 Enhancers Mini Stellar E2V 180w
- Antenna Advent 1,50m
- Spectrum analyzer Rohde & Schwarz FSH-3

Production:

- Analog mixing table
- 2 Bridges 2W GSM
- 2 Inserts RTC
- Prewiring for Codec RNIS
- Intercom system Prospect K6R

- Single-camera production

Contact:

Bernard Birebent
+33 (0)6 08 43 60 51
bernard.birebent@ampvisualtv.tv

www.ampvisualtv.tv/en/