



IXI 2 PROD

Cette station satellite a été conçue pour répondre aux captations sportives et événementielles qui demandent agilité et souplesse dans leurs déploiements.

Immatriculation Eutelsat: **F510**

Coordination: **+33 (0) 6 29 73 00 50**

N-1: **+33 (0) 6 34 27 04 36**



Captation multicaméras
jusqu'à 6 caméras



2+1 SD/HD MPEG2 / MPEG4
Modulable sur demande



Tri phase 32 Amp
5kVA UPS EATON
1 x 15 kVA generator




Mercedes Sprinter 519
DS-693-FA

Lengths 7.40 m
Widths 2.00 m
Height 3.30 m



Tender
AA-883-WQ

Lengths 7.40 m + 2m
Widths 2.40 m
Height 3.35 m



VIDEO

Workstation

1 SIMPLY TV ViBOX
8 channel In/out configurable
Ingest and replay server function
Video mixer
Audio mixer
Graphics / Logging
Panel 1 main 27" touch screen display

Cameras

6 SONY HXSC B75 fiber

Rec / Play

Option 4 AJA Ki-PRO recorder
Option 1 EVS LSM XT3 8-channel server

Router / monitor wall

48 x 48 RIEDEL Mediornet system
6 UP/DC Converteur
LSB VSM system control
SONY OLED monitor
IKEGAMI LCD ULE-215

Video devices

1 dual channel character generator
RIEDEL Mediornet infrastructure with optical technology
Sat & UHF demod receptors
TEKTRONIX WFM 5000 - VTM control measurement

SOUND

Audio mixer

YAMAHA DM 1000
16 faders
16 mic input / 8 auxillaries
MADI / Rocknet Interfaces

Audio monitoring

GENELEC 8330 monitors
FOSTEX monitors
RTW TM3 loudness monitor

Audio devices

Audio server
Intercom RIEDEL ARTIST 32 x 32 matrix
2 phone insert
2 ISDN and IP CODEC, with GSM bridge Wireless intercom system

POWER

Tri phase 380V 32A
2 x 5 kVA UPS EATON
1 x 15 kVA generator

UPLINK

Offset antenna
1 AVL 1812K 1,80 m

HPA
2 ADVANTECH 250W phase combiner

Encoders / Modulators
6 ATEME CM5000 SD/HD SAT/IP MPEG 2 & 4
4.2.0 - DVBS/S2

IRD
2 ATEME DR5000 SAT/IP

Toutes nos informations sont disponibles sur

▶▶▶ www.ampvisualtv.tv ◀◀◀